



Technical Data sonnenProtect 4000

Keep the lights on during a power outage with the sonnenProtect.

Nominal power	4,000 W
Nominal frequency	50 Hz
Output voltage	230 VAC / $\pm 10\%$
Overload (30 min)	max. 4,600 W
Max. output current (duration / 100 ms)	20 A / 23 A
Network configuration in emergency power mode	TN
Grid connection	Single phase, L / N / PE
Grid connection fuse	Miniature circuit breaker type B 20 A
Operating mode	Single phase emergency power supply via emergency power circuit(s). Switching to emergency power mode is automatically carried out by the storage system.
Switchover time	Normal operation to back-up power: approx. 5 s back-up power to normal operation approx. 3 s
Threshold performance	None (from 0 W)
Dimensions (cm) (H/W/D)	52/23/12
Weight (kg)	approx. 10
Protection class	II
Degree of protection	IP65
Necessary fault current monitoring	Residual current device (RCD) with max. 300 mA rated differential current; requirements on site must be observed
Environment	Indoor / outdoor areas
Degree of pollution	3
Temperature range	-5 °C - 50 °C
Max. relative humidity	100 %, condensing

We reserve the right to make technical changes and updates at any time. The specified values, services and other information as well as illustrations or drawings contained in this data sheet, brochures, and any other documents are only examples and are subject to ongoing revision and modifications. Unless we have expressly designated it as binding, this information does not constitute a warranty. The information in the binding order acceptance or the sales contract shall apply.